

BOILER-PRO™ 925

Hot Water Boiler Treatment Compound Corrosion and Scale Inhibitor Treatment

DESCRIPTION:

BOILER-PRO™ 925 is a concentrated, all organic, corrosion inhibitor, polymeric dispersant, and sludge conditioner for residential and small commercial, non-aluminum hot water boilers. The unique combination of additives provides scale prevention, corrosion protection, dispersancy, and sludge fluidization.

ADVANTAGES:

BOILER-PRO™ 925 is a formulated product that may be used in hot water boilers to help protect internal metals from corrosion due to dissolved oxygen and corrosive water. Additionally, the polymeric dispersants and peptizing agents help to keep the internal surfaces free of scale or other fouling materials. **BOILER-PRO™ 925** can also be used to treat chilled loop systems.

DIRECTIONS:

BOILER-PRO™ 925 should be slug fed to the system at a rate of 1 gallon per 50 gallons of system volume. Some separation of ingredients is normal during storage. Shake container before using. It is recommended that makeup water with hardness higher than 100 ppm (6-grains) should be softened prior to filling the boiler. High hardness can increase the potential for scale and sludge problems. Circulate the system fluid for several hours after treatment to thoroughly mix the product. If the boiler is vented to atmosphere, additional **BOILER-PRO™ 925** can be added for extra protection against oxygen corrosion damage. An annual maintenance dose of 1 gallon per 100 gallons of system volume is recommended to ensure long-term protection. Always add replacement inhibitor when fluid is lost or drained from the system.

NOTICE:

BOILER-PRO™ 925 is not antifreeze and offers no freeze protection. **BOILER-PRO™ 925** should be compatible with most antifreeze products. **Do not use with Onix tubing or aluminum boilers.** If product freezes, thaw completely and agitate to redissolve ingredients.

For technical support, call 1-417-862-2600.

