# RhoTherm<sup>™</sup> RTU

**RHOMAR WATER** 

Heat Transfer Fluids • Hydronic System Solutions

### Inhibited Ethylene Glycol Heat Transfer Fluid for Hydronic Heating and Cooling Systems

- Premixed and Ready-to-Use (RTU) System Fluid
- Blended with Virgin Ethylene Glycol and D.I. Water
- Contains Industrial Corrosion and Scale inhibitor Additives
- Protects Multiple Metals, Including Brass, Cast Iron, Copper and Stainless Steel
- Provides Years of Corrosion Protection
- Helps Keep Heat Exchange Surfaces Clean
- Maximizes System Efficiency
- Can Be Custom Blended to Any Glycol % As Needed By Customer
- Customized Freeze or Burst Protection

NADE IN US



Available in a variety of container sizes.

Rhomar Water, 2103 E Rockhurst St., Springfield, MO 65802 1-800-543-5975 • www.RhomarWater.com

## RhoTherm<sup>™</sup> RTU

RHOMAR WATER

Heat Transfer Fluids • Hydronic System Solutions

#### **DESCRIPTION:**

**RhoTherm™ RTU** is a premixed VIRGIN ETHYLENE GLYCOL antifreeze and heat transfer fluid specially blended with industrial corrosion and scale inhibitor additives. The glycol % for these customizable Ready-To-Use (RTU) blends can be tailored to your project needs.

#### **ADVANTAGES:**

**RhoTherm<sup>™</sup> RTU** can be used in hydronic heating and cooling systems. **RhoTherm<sup>™</sup> RTU** can be custom-blended to provide freeze protection and burst protection depending on the customer's needs. The additives in **RhoTherm<sup>™</sup> RTU** can help protect system metals including brass, cast iron, copper and stainless steel from corrosion and scale deposits.

#### **DIRECTIONS:**

All systems, new and existing, should be thoroughly cleaned and flushed using **Rhomar Water's Hydro-Solv**<sup>™</sup> cleaner prior to adding antifreeze. Properly cleaning the system will reduce the rate of corrosion and prolong the life of the antifreeze. **RhoTherm™ RTU** should be added to a clean system undiluted. Mixing with water will reduce the freeze/burst protection and the corrosion inhibitors.

#### NOTICE:

Any remaining fluid in the system will dilute the RhoTherm<sup>™</sup> RTU product resulting in a lower glycol percentage.

#### **ATTENTION:**

Variations of product color may be caused by manufacturing conditions, UV or sunlight exposure, or mixing with chlorinated water.

#### **REORDERS:**

Call 800-543-5975 or visit our website at www.RhomarWater.com.